





Item #	
Job	

# Model RHHT-C3 Series **Transport Cabinet**

## (With Gentle Convection Heat)

#### Performance Features

- Whisper Touch™ Gentle Convection maintains proper holding temperatures no matter the frequency of "in & out" to retrieve product
- Whisper Touch™ surrounds products with just the right amount of heat and air to maintain that just cooked look and flavor hour after hour
- Keeps fried foods hot and moist on the inside and crispy fried on the outside
- Ideal for fried foods, bulk pans of entrees and side dishes, pies, biscuits, even boxed pizza and pre-pack meals
- Maintains safe food holding temperatures for extended holding times: allowing for advanced preparation
- Ideally suited for school foodservice, catering, and banquet applications
- Hold temperature range: 75F 200F

#### **Construction Features**

- Self-contained power module for ease of service
- Fully insulated construction
- Type 304 welded steel body
- 12 gauge internal frame for strength
- Field Reversible Door
- Latch is magnetic/mechanical style
- Long lasting, high temperature silicone door gasket
- Four heavy duty, 6" swivel casters, two with brakes
- · Lift out interior for easy cleaning
- Transport latch/latches
- Perimeter bumper
- · Push/pull handles











### ROYALTON FOOD SERVICE FOURIER TO COMPANY





Madal Number	Pan Capacity Per Holding Cabinet Pan Spacing Per Holding Cabinet C3US 61/4" Fixed						t (H)		(w)	Ith (BW)	Wt. (lbs)	ts	atts Per mpartment	Amps Per Compartment	Phase	ord Plug MA)
Model Number	18x26x1 12 Sheet			0x2½ an	12x20x4 Pan		eight	epth	/idth	Width	ing	Volts	یّ ≷		lertz/l	er Co
	STD *	мах	STD *	мах	STD *	мах	Ĭ	Q	>	Base	Shippi		Total Holding	Total Holding	He	Powe
RHHT-2000-C3US	7	7	14	14	14	14	61½	35 <sup>3</sup> / <sub>8</sub>	26	29	437	120	2000	16.6	50/60 1Ø	5-20P

### **Bidding Specifications**

Royalton Model # RHHT-\_\_\_-C3US\_\_, gentle convection holding cabinet, fully insulated, all stainless steel construction, single door with solid-state controls incorporated in the self-contained, removable power module. Digital temperature readout.

Interior for:

Model RHH-2000-C3UST

Capacity:

(14) 12x20x4

(7) 18x26x1

(See drawing on the right)

#### \* Options

- Dutch Doors
- Latch Magnetic/Mechanical w/Key Lock
- Interiors available for:

12x20x2½

12x20x4

12x20x4

18x26x1

or any combination of these

pans

\*Consult Factory

